## NSN 5306-00-685-1536

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-685-1536 **Thread Direction:** Right-hand Thread Length: 0.415 inches Fastener Length: 0.890 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.260 inches Width Between Flats: 0.247 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** 0.045 inches **First Diameter From Head:** 0.166 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.475 inches **Thread Diameter:** 0.190 inches **Nonstandard Thread Pitch Diameter:** +0.1644/+0.1667 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 36.0 rockwell c Minimum Yield Strength: 85000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams 5735 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5306-00-685-1536

Externally Relieved Body Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0