NSN 5306-00-685-2774

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-685-2774

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.425 inches |
| Fastener Length: |
| 0.487 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.125 inches and 0.140 inches |
| Width Between Flats: |
| Between 0.430 inches and 0.439 inches |
| Hole Diameter: |
| 0.047 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 0.062 inches |
| Hole Quantity: |
| 3 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon flats |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams4967 assn standard single material response |
| Thread Series Designator: |
| Unf |
| Specification Data: |
| 80205-nas674 professional/industrial association standard |
| Shelf Life: |
| N/a |
| |

NSN 5306-00-685-2774

Machine Bolt - Page 2 of 2



| | • • | | | | | | |
|----|-----|----|----|----|-----|-----|----|
| ın | 1+ | Of | ΝЛ | ດລ | CI. | ırı | ο. |
| | | | | | | | |

--

Demilitarization:

No

Fiig:

A003b0