

View Online at <https://aerobasegroup.com/nsn/5306-00-685-7449>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.710 inches and 0.760 inches

Fastener Length:

Between 1.532 inches and 1.562 inches

Head Style:

Hexagon

Head Height:

Between 0.250 inches and 0.265 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Hole Diameter:

0.111 inches

Grip Diameter:

Between 0.4985 inches and 0.4995 inches

Thread Diameter:

0.500 inches

Grip Length:

Between 0.802 inches and 0.822 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Hole Configuration Style:

Hexagon corners

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1308 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.