Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-687-6043

Thread	Class:
3a	
Thread	Direction:
Right-ha	and
Thread	Length:
0.430 ir	nches
Fasten	er Length:
1.920 ir	nches
Head S	tyle:
Hexago	n
Head H	leight:
Betwee	n 0.169 inches and 0.171 inches
Width E	Between Flats:
Betwee	n 0.428 inches and 0.440 inches
First Di	iameter From Head:
Betwee	n 0.248 inches and 0.249 inches
Second	Diameter From Head:
0.210 ir	nches
Гhird D	Diameter From Head:
Betwee	n 0.248 inches and 0.249 inches
Distanc	ce From Largest Bearing Surface Of Head To End Of First Diameter:
).440 ir	nches
Distanc	ce From Largest Bearing Surface Of Head To End Of Second Diameter:
.206 ir	nches
Distanc	ce From Largest Bearing Surface Of Head To End Of Third Diameter:
1.490 ir	nches
Thread	Diameter:
0.250 ir	nches
Thread	y Qty Per Inch (tpi):
28	
Hardne	ess Rating:
28.0 roc	ckwell c and 38.0 rockwell c
Externa	ally Relieved Body Diameter Quantity:
3	
Materia	ıl:
Nickel a	alloy x-750
Surface	e Treatment:
Passiva	ate
Thread	Series Designator:
Unf	
Shelf L	ife:
N/a	

NSN 5306-00-687-6043

Externally Relieved Body Bolt - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0