NSN 5306-00-687-6285

Internal Wrenching Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-687-6285

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.562 inches |
| Fastener Length: |
| Between 2.137 inches and 2.147 inches |
| Head Diameter: |
| Between 0.521 inches and 0.531 inches |
| Head Height: |
| 0.312 inches |
| Shank Unthreaded Hole Diameter: |
| 0.076 inches first hole |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.312 inches |
| Width Across Flats: |
| Between 0.219 inches and 0.221 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 40.0 rockwell c |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 2.000 inches first hole |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |