

View Online at <https://aerobasegroup.com/nsn/5306-00-687-6722>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.602 inches and 0.662 inches

**Fastener Length:**

Between 2.117 inches and 2.147 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.172 inches and 0.204 inches

**Width Between Flats:**

Between 0.492 inches and 0.501 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 1.485 inches and 1.515 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

248.0 brinell standard and 341.0 brinell standard

**Product Name:**

Navy special project

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5735 assn standard 1st material response or ams 5737 assn standard 2nd material response or ams 5733 assn standard 3rd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Thread Series Designator:**

Unf

**Specification Data:**

80205-nas1005 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5002 spec.