## NSN 5306-00-687-7116

Machine Bolt - Page 1 of 2

**Thread Direction:** 





## **Right-hand Thread Length:** Between 0.978 inches and 1.038 inches Fastener Length: Between 1.558 inches and 1.568 inches Head Style: Double hexagon w/hole **Head Height:** Between 0.360 inches and 0.380 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.490 inches and 0.500 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches **Thread Diameter:** 0.312 inches Grip Length: Between 0.530 inches and 0.580 inches **Features Provided:** Finished head Nonstandard Thread Pitch Diameter: +0.2797/+0.2824 inches Thready Qty Per Inch (tpi): 24 Surface Finish: 63.0 microinches grip Material: Steel **Material Specification:** C50t22 fscm 07482 mfr ref single material response Surface Treatment: Nickel Surface Treatment Specification: Ams assn standard single treatment response **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure:

--

## NSN 5306-00-687-7116

Machine Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

