

View Online at <https://aerobasegroup.com/nsn/5306-00-687-7388>

Thread Direction:

Right-hand

Thread Length:

0.673 inches

Fastener Length:

Between 1.230 inches and 1.250 inches

Head Style:

Round w/wrench flats

Head Diameter:

Between 0.550 inches and 0.570 inches

Head Height:

Between 0.180 inches and 0.200 inches

Width Between Flats:

0.300 inches

First Diameter From Head:

Between 0.309 inches and 0.312 inches

Second Diameter From Head:

Between 0.235 inches and 0.245 inches

Third Diameter From Head:

Between 0.309 inches and 0.312 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.120 inches and 0.140 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.250 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

0.454 inches

Thread Diameter:

0.312 inches

Nonstandard Thread Pitch Diameter:

+0.2797/+0.2824 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

142000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Externally Relieved Body Diameter Quantity:

3

Material:

Steel comp 601

Material Specification:

Ams 6304 assn standard single material response

Surface Treatment:

Copper and cadmium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0