

View Online at <https://aerobasegroup.com/nsn/5306-00-687-7391>

**Thread Class:**

1a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.740 inches and 0.760 inches

**Fastener Length:**

Between 0.740 inches and 0.760 inches

**Head Style:**

Hexagon

**Head Height:**

0.330 inches

**Width Between Flats:**

0.309 inches

**Extended Washer Diameter:**

0.438 inches

**Extended Washer Thickness:**

0.065 inches

**Shank Unthreaded Hole Diameter:**

0.069 inches first hole

**Thread Diameter:**

0.250 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

142000 pounds per square inch

**Hardness Rating:**

30.0 rockwell c and 38.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.750 inches first hole

**Material:**

Steel comp 601

**Material Specification:**

Ams 6304 assn standard single material response

**Surface Treatment:**

Nickel and cadmium

**Surface Treatment Specification:**

Ams 2416 assn standard all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0