

View Online at <https://aerobasegroup.com/nsn/5306-00-692-7528>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.740 inches

Fastener Length:

11.042 inches

Head Style:

Round w/wrench flats

Head Diameter:

2.875 inches

Head Height:

0.100 inches

Width Between Flats:

2.400 inches

Shoulder Diameter:

0.887 inches first shoulder and 0.897 inches first shoulder

Shoulder Length:

9.120 inches first shoulder and 9.130 inches first shoulder

Shank Unthreaded Hole Diameter:

0.008 inches first hole

Thread Diameter:

0.073 inches

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

180000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

12.304 inches first hole

Shoulder Shape:

Round first shoulder

Special Features:

One hole in head; threaded 0.750 in. Dia.; 10 threads per in.; thread class 2a; 0.750 in. Depth

Material:

Steel comp 4340

Material Specification:

Mil-s-5000 cond. F military specification single material response

Surface Treatment:

Cadmium head

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.