

View Online at <https://aerobasegroup.com/nsn/5306-00-693-6295>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.312 inches and 0.453 inches

Eye Inside Diameter:

Between 0.277 inches and 0.290 inches

Shoulder Thickness:

0.062 inches

Shank Length:

Between 1.015 inches and 1.062 inches

Eye Stock Diameter:

Between 0.089 inches and 0.099 inches

Eye Stock Thickness:

0.094 inches

Shoulder Diameter:

0.438 inches

Shank Unthreaded Hole Diameter:

0.060 inches and 0.080 inches first hole

Overall Length:

Between 1.793 inches and 1.816 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Distance From Center Of Eye To Shank End:

Between 1.574 inches and 1.597 inches

Eye Outside Width:

0.438 inches

Product Name:

Navy special project

Material:

Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 3 federal specification single treatment response

Style Designator:

Round, closed w/shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.