

View Online at <https://aerobasegroup.com/nsn/5306-00-693-6295>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.312 inches and 0.453 inches

**Eye Inside Diameter:**

Between 0.277 inches and 0.290 inches

**Shoulder Thickness:**

0.062 inches

**Shank Length:**

Between 1.015 inches and 1.062 inches

**Eye Stock Diameter:**

Between 0.089 inches and 0.099 inches

**Eye Stock Thickness:**

0.094 inches

**Shoulder Diameter:**

0.438 inches

**Shank Unthreaded Hole Diameter:**

0.060 inches and 0.080 inches first hole

**Overall Length:**

Between 1.793 inches and 1.816 inches

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Center Of Eye To Shank End:**

Between 1.574 inches and 1.597 inches

**Eye Outside Width:**

0.438 inches

**Product Name:**

Navy special project

**Material:**

Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl 3 federal specification single treatment response

**Style Designator:**

Round, closed w/shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.