NSN 5306-00-693-7440

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-693-7440 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.118 inches and 0.133 inches **Fastener Length:** 1.700 inches **Head Style:** Dee **Head Diameter:** 0.620 inches **Head Height:** 0.060 inches **Distance From Centerline To Flat:** Between 0.250 inches and 0.255 inches **Shoulder Diameter:** 0.3110 inches first shoulder and 0.3120 inches first shoulder **Shoulder Length:** 1.380 inches first shoulder and 1.385 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.075 inches first hole and 0.078 inches first hole **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.620 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp 4140 **Material Specification:** Mil-s-5626 military specification single material response **Surface Treatment:** Cadmium or chromium **Surface Treatment Specification:** An-p-61 assn standard 1st treatment response or mil-p-6871 military specification 2nd treatment response **Thread Series Designator:**

Unf

Shelf Life:

N/a

NSN 5306-00-693-7440

Shoulder Bolt - Page 2 of 2



Unit Of Measure	ι	ι	J	n	it	Of	Measure:	
-----------------	---	---	---	---	----	----	----------	--

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.