

View Online at <https://aerobasegroup.com/nsn/5306-00-693-7443>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.590 inches

Fastener Length:

5.620 inches

Head Style:

Hexagon

Head Height:

0.200 inches

Width Between Flats:

2.060 inches

Shoulder Diameter:

Between 1.622 inches and 1.623 inches

Shoulder Length:

Between 4.815 inches and 4.820 inches

Shank Unthreaded Hole Diameter:

0.140 inches first hole and 0.144 inches first hole

Concentric Hole Depth:

4.440 inches

Concentric Hole Diameter:

1.000 inches

Thread Diameter:

1.125 inches

Thready Qty Per Inch (tpi):

12

Hardness Rating:

34.0 rockwell c and 39.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.400 inches first hole

Material:

Steel

Material Specification:

Mil-s-5000 cond c military specification single material response

Surface Treatment:

Cadmium head

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.