## NSN 5306-00-695-4386

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-695-4386 **Thread Class:** 1a **Thread Direction:** Right-hand Thread Length: 0.461 inches **Fastener Length:** Between 5.396 inches and 5.416 inches **Head Style:** Hexagon **Head Height:** Between 0.318 inches and 0.338 inches Width Between Flats: Between 0.618 inches and 0.627 inches **Hole Diameter:** 0.183 inches First Diameter From Head: Between 0.445 inches and 0.449 inches **Second Diameter From Head:** Between 0.357 inches and 0.361 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.280 inches and 0.300 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 4.820 inches **Thread Diameter:** 0.438 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Hole Configuration Style:** Hexagon longitudinal hole **Externally Relieved Body Diameter Quantity:** 2 Material:

Steel comp 8740

**Material Specification:** 

Ams 6322 assn standard single material response

## NSN 5306-00-695-4386

Externally Relieved Body Bolt - Page 2 of 2



| Surface Treatment:        |
|---------------------------|
| Cadmium                   |
| Thread Series Designator: |
| Unf                       |
| Shelf Life:               |
| N/a                       |
| Unit Of Measure:          |
|                           |
| Demilitarization:         |
| No                        |

Fiig: A003b0