NSN 5306-00-697-0128

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-697-0128

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.344 inches |
| Fastener Length: |
| 1.188 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| 0.094 inches |
| Width Between Flats: |
| 0.625 inches |
| Hole Diameter: |
| 0.046 inches |
| Grip Diameter: |
| 0.1894 inches |
| Single Shear Strength: |
| 14300 pounds per square inch |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| 0.844 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hole Configuration Style: |
| Hexagon corners |
| Material: |
| Steel comp 4130 |
| Material Specification: |
| Mil-s-6758, f4 military specification single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |

Qq-p-416 type 2 cl 3 federal specification single treatment response

NSN 5306-00-697-0128

Shear Bolt - Page 2 of 2



| Thread Series Designator: |
|-----------------------------|
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |
| Demilitarization: |
| Demilitarization: No |
| |

Mil-std (military Standard):

Mil-s-6758 spec.