NSN 5306-00-701-2250

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-701-2250 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.209 inches and 0.251 inches **Fastener Length:** Between 1.100 inches and 1.110 inches **Head Style:** Hexagon **Head Height:** Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.859 inches and 0.891 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch Material: Aluminum alloy 2024 **Material Specification:** Qq-a-200 federal specification 1st material response or qq-a-225 federal specification 2nd material response or qq-a-430 federal specification 3rd material response **Surface Treatment:** Anodize or chromate **Surface Treatment Specification:** Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

No

A003b0

NSN 5306-00-701-2250

Machine Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.