## NSN 5306-00-702-6507

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-702-6507 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 0.750 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.330 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **First Diameter From Head:** Between 0.221 inches and 0.231 inches **Second Diameter From Head:** Between 0.246 inches and 0.249 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.050 inches and 0.070 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.250 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Hardness Rating: 34.0 rockwell c and 42.0 rockwell c **Externally Relieved Body Diameter Quantity:** 2 Material: Nickel alloy **Material Specification:** Ams 5708 assn standard single material response **Surface Treatment: Passivate** 

Unf

**Thread Series Designator:** 

## NSN 5306-00-702-6507

Externally Relieved Body Bolt - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0