

View Online at <https://aerobasegroup.com/nsn/5306-00-706-2280>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.562 inches

**Distance From Inside Center Of Bend To Bolt End:**

1.469 inches

**Inside Distance Between Shanks:**

1.062 inches

**Thread Diameter:**

0.190 inches

**Thread Qty Per Inch (tpi):**

32

**Special Features:**

Shoulder located 0.688 inches from end

**Material:**

Steel comp 1017 or steel comp 1023 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1021 or steel comp 1524 or steel comp 1211 or steel

**Material Specification:**

Qq-s-631 federal specification 1st material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal specification 3rd material response or qq-s-634 federal specification 4th material response or qq-s-634 federal specification 5th material response or qq-s-634 federal specification 6th material response or qq-s-634 federal specification 7th material response or qq-s-634 federal specification 8th material response or qq-s-634 federal specification 9th material response or qq-s-633 federal specification 10th material response or qq-s-633 federal specification 11th material response or qq-s-637 federal specification 12th material response or qq-s-637 federal specification 13th material response

**Surface Treatment:**

Cadmium or zinc

**Style Designator:**

Round bend

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0