## NSN 5306-00-709-1474

Ribbed Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-709-1474 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.875 inches **Fastener Length:** Between 1.375 inches and 1.391 inches **Head Style:** Flat chamfer **Head Diameter:** 0.625 inches **Head Height:** Between 0.182 inches and 0.192 inches **Shoulder Diameter:** 0.429 inches first shoulder and 0.434 inches first shoulder **Shoulder Length:** 0.365 inches first shoulder and 0.375 inches first shoulder **Rib Major Diameter:** Between 0.429 inches and 0.434 inches **Rib Length:** Between 0.365 inches and 0.375 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 28.0 rockwell c and 36.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 4140 **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life:

N/a

## NSN 5306-00-709-1474

Ribbed Shoulder Bolt - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0