NSN 5306-00-709-2996

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-709-2996 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.498 inches **Fastener Length:** 3.173 inches **Head Style:** Hexagon **Head Height:** 0.220 inches Width Between Flats: Between 0.553 inches and 0.565 inches **Shoulder Diameter:** 0.373 inches first shoulder and 0.374 inches first shoulder **Shoulder Length:** 2.675 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.077 inches first hole and 0.082 inches first hole **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 260000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 2.993 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp 4340 **Material Specification:** Mil-s-5000 military specification single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5306-00-709-2996

Shoulder Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.