NSN 5306-00-721-5685

Internal Wrenching Bolt - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/5506-00-721-5665
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.600 inches and 1.650 inches
Fastener Length:
Between 4.985 inches and 5.015 inches
Head Style:
Bevel-conical Seven Seve
Head Diameter:
Between 2.115 inches and 2.125 inches
Head Height:
1.250 inches
Hole Diameter:
0.055 inches
Internal Drive Style:
Hexagon
Thread Diameter:
1.250 inches
Width Across Flats:
Between 1.001 inches and 1.005 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
12
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
34.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Round longitudinal hole
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:

Qq-p-416, type 2 cl 3 federal specification single treatment response

NSN 5306-00-721-5685

Internal Wrenching Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-s-5626 spec.