## NSN 5306-00-722-8374



Shoulder Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-722-8374 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.440 inches and 0.520 inches **Fastener Length:** Between 5.250 inches and 5.290 inches **Head Style:** Hexagon **Head Height:** Between 0.183 inches and 0.203 inches Width Between Flats: Between 0.552 inches and 0.564 inches **Shoulder Diameter:** 0.374 inches first shoulder and 0.375 inches first shoulder **Shoulder Length:** 4.390 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.070 inches first hole **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 5.108 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp 8740 **Material Specification:** Mil-s-5000 military specification single material response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5306-00-722-8374

Shoulder Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.