## NSN 5306-00-723-7192

Internal Wrenching Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-723-7192



**Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.354 inches **Fastener Length:** 1.125 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.221 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **First Diameter From Head:** Between 0.1353 inches and 0.1380 inches **Second Diameter From Head:** 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.531 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.751 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.093 inches and 0.094 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 304 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

## NSN 5306-00-723-7192

Internal Wrenching Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.