

View Online at <https://aerobasegroup.com/nsn/5306-00-723-9466>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.215 inches

**Fastener Length:**

0.860 inches

**Head Diameter:**

0.625 inches

**Head Height:**

0.094 inches

**Groove Diameter:**

Between 0.245 inches and 0.255 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole and 0.086 inches first hole

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.750 inches first hole

**Material:**

Steel comp 8740 or steel comp 8630

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0