

View Online at <https://aerobasegroup.com/nsn/5306-00-725-5844>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.624 inches and 0.688 inches

**Fastener Length:**

Between 2.328 inches and 2.360 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.234 inches and 0.266 inches

**Width Between Flats:**

Between 0.615 inches and 0.627 inches

**Shoulder Diameter:**

0.4490 inches first shoulder and 0.4495 inches first shoulder

**Shoulder Length:**

1.672 inches first shoulder and 1.704 inches first shoulder

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 33.0 rockwell c

**Shoulder Shape:**

Round first shoulder

**Special Features:**

Cad plate 0.00015 in. Maximum thk

**Material:**

Steel

**Material Specification:**

Mil-s-6758, cond c military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.