## NSN 5306-00-725-6614

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-725-6614

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.640 inches   |
| Fastener Length:   |
| 0.828 inches   |
| Head Style:  |
| Hexagon  |
| Head Height:   |
| Between 0.203 inches and 0.235 inches                            |
| Width Between Flats:   |
| Between 0.553 inches and 0.565 inches                            |
| Hole Diameter:   |
| 0.070 inches   |
| Shank Unthreaded Hole Diameter:                                  |
| 0.106 inches first hole  |
| Thread Diameter:   |
| 0.375 inches   |
| Grip Length:   |
| 0.188 inches   |
| Hole Quantity:   |
| 1  |
| Ноlе Туре:   |
| Drilled  |
| Features Provided:   |
| Finished head  |
| Thready Qty Per Inch (tpi):                                      |
| 24   |
| Min. Tensile Strength (psi):                                     |
| 125000 pounds per square inch                                    |
| Hardness Rating:   |
| 26.0 rockwell c and 32.0 rockwell c                              |
| Hole Configuration Style:  |
| Hexagon flats  |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 0.626 inches first hole  |
| Material:  |
| Stainless steel  |
| Material Specification:  |
|  |

Qq-s-770 federal specification single material response

## NSN 5306-00-725-6614

Machine Bolt - Page 2 of 2

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

