

View Online at <https://aerobasegroup.com/nsn/5306-00-725-8515>

Thread Direction:

Right-hand

Thread Length:

Between 0.760 inches and 0.802 inches

Fastener Length:

Between 1.052 inches and 1.072 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.320 inches and 0.340 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

Extended Washer Diameter:

Between 0.428 inches and 0.448 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

Hole Diameter:

0.062 inches

Thread Diameter:

0.250 inches

Grip Length:

Between 0.250 inches and 0.312 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Nonstandard Thread Pitch Diameter:

+0.2213/+0.2238 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

142000 pounds per square inch

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Material:

Steel comp 601

Material Specification:

Ams 6304 assn standard single material response

Surface Treatment:

Nickel and cadmium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0