

View Online at <https://aerobasegroup.com/nsn/5306-00-726-5632>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.475 inches and 0.490 inches

**Fastener Length:**

Between 1.075 inches and 1.085 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.302 inches and 0.312 inches

**Head Height:**

0.120 inches

**First Diameter From Head:**

Between 0.185 inches and 0.190 inches

**Second Diameter From Head:**

Between 0.121 inches and 0.124 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.975 inches and 0.990 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 1.075 inches and 1.085 inches

**Criticality Code Justification:**

Feat

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

O/a lg of first dia from head, rd w/wrench flats shape 0.142 in. Min 0.145 in. Max w, between flats

**Material:**

Steel comp 1018 or steel comp 1022

**Surface Treatment:**

Phosphate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0