## NSN 5306-00-726-5632

Externally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-726-5632 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.475 inches and 0.490 inches **Fastener Length:** Between 1.075 inches and 1.085 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.302 inches and 0.312 inches **Head Height:** 0.120 inches **First Diameter From Head:** Between 0.185 inches and 0.190 inches **Second Diameter From Head:** Between 0.121 inches and 0.124 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.975 inches and 0.990 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.075 inches and 1.085 inches **Criticality Code Justification:** Feat **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** O/a Ig of first diafrom head, rd w/wrench flats shape 0.142 in. Min 0.145 in.Max w, between flats Material: Steel comp 1018 or steel comp 1022 **Surface Treatment:** Phosphate **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A003b0