

View Online at <https://aerobasegroup.com/nsn/5306-00-726-7710>

**Thread Direction:**

Right-hand

**Thread Length:**

0.430 inches

**Fastener Length:**

0.620 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.260 inches

**Width Between Flats:**

0.247 inches

**Extended Washer Diameter:**

0.375 inches

**Extended Washer Thickness:**

0.045 inches

**First Diameter From Head:**

Between 0.161 inches and 0.171 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.190 inches

**Thread Diameter:**

0.190 inches

**Nonstandard Thread Pitch Diameter:**

+0.1644/+0.1667 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

32.0 rockwell c and 36.0 rockwell c

**Minimum Yield Strength:**

130000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 601

**Material Specification:**

Ams 6304 assn standard single material response

**Surface Treatment:**

Nickel

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0