NSN 5306-00-732-1422

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-732-1422

Thread Direction:
Right-hand
Thread Length:
Between 0.282 inches and 0.365 inches
Fastener Length:
Between 0.365 inches and 0.385 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.365 inches and 0.385 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.490 inches and 0.510 inches
Extended Washer Thickness:
Between 0.070 inches and 0.080 inches
Thread Diameter:
0.312 inches
Features Provided:
Finished head
Nonstandard Thread Pitch Diameter:
+0.2797/+0.2824 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
105000 pounds per square inch
Hardness Rating:
30.0 rockwell c and 38.0 rockwell c
Material:
Steel comp 601
Material Specification:
Ams 6304 assn standard single material response
Surface Treatment:
Nickel and cadmium
Surface Treatment Specification:
Ams 2416 assn standard all treatment responses
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

NSN 5306-00-732-1422

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0