NSN 5306-00-732-2782

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-732-2782 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.544 inches **Fastener Length:** 1.982 inches **Head Style:** Hexagon **Head Height:** 0.156 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Thread Diameter:** 0.250 inches **Grip Length:** 1.438 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 140000 pounds per square inch **Special Features:** Tensile strength at room temperature Material: Iron alloy 660 or steel comp 630 **Material Specification:** Ams 5735 assn standard 1st material response secondary washer or ams 5737 assn standard 1st material response secondary washer or ams 5733 assn standard 2nd material response secondary washer **Surface Treatment: Passivate Surface Treatment Specification:** Mil-s-5002 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5306-00-732-2782

Machine Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.