NSN 5306-00-732-9313

Internal Wrenching Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-732-9313



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 1.162 inches and 1.212 inches Fastener Length: Between 4.047 inches and 4.077 inches **Head Style: Bevel-conical Head Diameter:** Between 1.428 inches and 1.438 inches **Head Height:** 0.875 inches Hole Diameter: 0.055 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.875 inches Width Across Flats: Between 0.625 inches and 0.629 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Hole Configuration Style: Round Material: Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416 type 2 cl 2 federal specification single treatment response

NSN 5306-00-732-9313

Internal Wrenching Bolt - Page 2 of 2



Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.