

View Online at <https://aerobasegroup.com/nsn/5306-00-737-9523>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.340 inches and 0.400 inches

**Fastener Length:**

Between 0.740 inches and 0.760 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.115 inches and 0.135 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Shank Unthreaded Hole Diameter:**

0.062 inches first hole and 0.072 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.360 inches and 0.400 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

30.0 rockwell c and 38.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.635 inches first hole and 0.645 inches first hole

**Material:**

Steel comp 431

**Material Specification:**

Ams 5628 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0