

View Online at <https://aerobasegroup.com/nsn/5306-00-740-7641>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.796 inches and 0.828 inches

**Fastener Length:**

Between 2.609 inches and 2.641 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.484 inches and 0.516 inches

**Width Between Flats:**

Between 1.108 inches and 1.125 inches

**First Diameter From Head:**

Between 0.870 inches and 0.875 inches

**Second Diameter From Head:**

Between 0.767 inches and 0.777 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.671 inches and 0.703 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 1.781 inches and 1.845 inches

**Thread Diameter:**

0.875 inches

**Thready Qty Per Inch (tpi):**

14

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel comp 1340 or steel comp 4140 or steel comp 8640 or steel comp 8740

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Qq-p-416 federal specification 1st treatment response or qq-z-325 federal specification 2nd treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0