

View Online at <https://aerobasegroup.com/nsn/5306-00-740-7641>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.796 inches and 0.828 inches

Fastener Length:

Between 2.609 inches and 2.641 inches

Head Style:

Dished hexagon

Head Height:

Between 0.484 inches and 0.516 inches

Width Between Flats:

Between 1.108 inches and 1.125 inches

First Diameter From Head:

Between 0.870 inches and 0.875 inches

Second Diameter From Head:

Between 0.767 inches and 0.777 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.671 inches and 0.703 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 1.781 inches and 1.845 inches

Thread Diameter:

0.875 inches

Thready Qty Per Inch (tpi):

14

Externally Relieved Body Diameter Quantity:

2

Material:

Steel comp 1340 or steel comp 4140 or steel comp 8640 or steel comp 8740

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416 federal specification 1st treatment response or qq-z-325 federal specification 2nd treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0