NSN 5306-00-740-7641

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-740-7641 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.796 inches and 0.828 inches **Fastener Length:** Between 2.609 inches and 2.641 inches **Head Style:** Dished hexagon **Head Height:** Between 0.484 inches and 0.516 inches Width Between Flats: Between 1.108 inches and 1.125 inches **First Diameter From Head:** Between 0.870 inches and 0.875 inches **Second Diameter From Head:** Between 0.767 inches and 0.777 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.671 inches and 0.703 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.781 inches and 1.845 inches **Thread Diameter:** 0.875 inches Thready Qty Per Inch (tpi): 14 **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 1340 or steel comp 4140 or steel comp 8640 or steel comp 8740 **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416 federal specification 1st treatment response or qq-z-325 federal specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5306-00-740-7641

Externally Relieved Body Bolt - Page 2 of 2



Fiig:

A003b0