

View Online at <https://aerobasegroup.com/nsn/5306-00-740-9555>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

1.187 inches

**Fastener Length:**

2.812 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

1.312 inches

**Head Height:**

0.312 inches

**Shoulder Diameter:**

0.973 inches first shoulder and 0.977 inches first shoulder

**Shoulder Length:**

1.312 inches first shoulder

**Rib Major Diameter:**

Between 1.019 inches and 1.024 inches

**Rib Length:**

Between 0.422 inches and 0.454 inches

**Distance From Largest Diameter Of Bearing Surface Of Head To Ribs:**

0.375 inches

**Rib Quantity:**

36

**Thread Diameter:**

0.750 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

110000 pounds per square inch

**Hardness Rating:**

223.0 brinell standard and 277.0 brinell standard

**Rib Included Angle:**

90.0 degrees

**Shoulder Shape:**

Ribbed first shoulder

**Material:**

Steel comp 4427 or steel comp 4620h or steel comp 8620h or steel comp 8622h

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0