

View Online at <https://aerobasegroup.com/nsn/5306-00-741-1026>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.625 inches

Fastener Length:

1.188 inches

Head Style:

Hexagon

Head Height:

0.188 inches

Width Between Flats:

0.562 inches

Shoulder Diameter:

0.407 inches first shoulder and 0.410 inches first shoulder

Shoulder Length:

1.812 inches first shoulder

Rib Major Diameter:

Between 0.422 inches and 0.432 inches

Rib Length:

0.125 inches

Distance From Largest Diameter Of Bearing Surface Of Head To Ribs:

0.094 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

20.0 rockwell c and 26.0 rockwell c

Shoulder Shape:

Ribbed first shoulder

Material:

Steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541 or steel comp 1042 or steel comp 1043 or steel comp 1045

Material Specification:

66 federal standard all material responses or aisi assn standard all material responses or sae assn standard all material responses

Surface Treatment:

Cadmium or zinc

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0