NSN 5306-00-741-1426



Ribbed Shoulder Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-741-1426 **Thread Direction:** Right-hand Thread Length: Between 0.875 inches and 0.937 inches Fastener Length: Between 1.250 inches and 1.312 inches **Head Style:** Pan no. 2 **Head Diameter:** 0.625 inches **Head Height:** 0.188 inches **Shoulder Diameter:** 0.438 inches first shoulder **Shoulder Length:** 0.188 inches first shoulder **Rib Major Diameter:** Between 0.490 inches and 0.495 inches **Rib Length:** 0.156 inches Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: 0.031 inches **Thread Diameter:** 0.375 inches **Nonstandard Thread Pitch Diameter:** +0.3446/+0.3479 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 110000 pounds per square inch Hardness Rating: 20.0 rockwell c and 25.0 rockwell c **Shoulder Shape:** Ribbed first shoulder Material: Steel comp 1040 **Material Specification:** Sae assn standard single material response **Thread Series Designator:** Unf

N/a

Shelf Life:

NSN 5306-00-741-1426

Ribbed Shoulder Bolt - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0