NSN 5306-00-753-8725

Internally Relieved Body Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-753-8725 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** 0.500 inches **Head Style:** Hexagon **Head Height:** 0.500 inches Width Between Flats: 0.750 inches **Concentric Hole Diameter:** 0.344 inches **End Application:** W/s: truck, dump, 5-ton, 6x6 (m929, m930); truck, cargo, dropside, 5-ton, 6x6 (m813a1, m-9239, m-925); truck, cargo, dropside, xlwb, 5-ton, 6x6 (m814, m927, m928); chaparral/vulcan ads/ssamd; truck, wrecker, 5-ton (m936); maint facility, night sight (nsfm), tam e10227; airborne mobile dir air spt ctl (2id), (02mjul83)(an/uyq-3a); truck, cargo, dropside, 2 1/2-ton 6x6 w/e; truck, cargo, 5-ton, 6x6, xlwb w/e; aircraft, t-39 **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): 11 **Special Features:** Thread relief under head 0.500 in. Diameter by 0.125 in. W Steel comp 1211 or steel comp 1212 or steel comp 1213 **Surface Treatment:** Cadmium **Style Designator:** Concentric hole unthreaded **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

No

A003b0