

View Online at <https://aerobasegroup.com/nsn/5306-00-753-8725>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

0.500 inches

Head Style:

Hexagon

Head Height:

0.500 inches

Width Between Flats:

0.750 inches

Concentric Hole Diameter:

0.344 inches

End Application:

W/s: truck, dump, 5-ton, 6x6 (m929, m930); truck, cargo, dropside, 5-ton, 6x6 (m813a1, m-9239, m-925); truck, cargo, dropside, xlwb, 5-ton, 6x6 (m814, m927, m928); chaparral/vulcan ads/ssamd; truck, wrecker, 5-ton (m936); maint facility, night sight (nsfm), tam e10227; airborne mobile dir air spt ctl (2id), (02mjul83)(an/uyq-3a); truck, cargo, dropside, 2 1/2-ton 6x6 w/e; truck, cargo, 5-ton, 6x6, xlwb w/e; aircraft, t-39

Thread Diameter:

0.625 inches

Thready Qty Per Inch (tpi):

11

Special Features:

Thread relief under head 0.500 in. Diameter by 0.125 in. W

Material:

Steel comp 1211 or steel comp 1212 or steel comp 1213

Surface Treatment:

Cadmium

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0