NSN 5306-00-757-0605

Ribbed Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-757-0605

Thread Direction:
Left-hand
Thread Length:
1.062 inches
Fastener Length:
Between 1.969 inches and 2.031 inches
Head Style:
Flat chamfer
Head Diameter:
Between 1.141 inches and 1.172 inches
Head Height:
0.312 inches
Shoulder Diameter:
0.876 inches first shoulder and 0.878 inches first shoulder
Shoulder Length: 0.374 inches first shoulder and 0.390 inches first shoulder
Rib Major Diameter:
Between 0.910 inches and 0.920 inches
Rib Length:
0.500 inches
Distance From Largest Diameter Of Bearing Surface Of Head To Ribs:
0.125 inches
Rib Quantity:
Rib Quantity: 40
Rib Quantity: 40 Thread Diameter:
Rib Quantity: 40 Thread Diameter: 0.750 inches
Rib Quantity: 40 Thread Diameter: 0.750 inches Features Provided:
Rib Quantity: 40 Thread Diameter: 0.750 inches Features Provided: Casehardened
Rib Quantity: 40 Thread Diameter: 0.750 inches Features Provided: Casehardened Nonstandard Thread Pitch Diameter:
Rib Quantity:40Thread Diameter:0.750 inchesFeatures Provided:CasehardenedNonstandard Thread Pitch Diameter:+0.7044/+0.7084 inches
Rib Quantity:40Thread Diameter:0.750 inchesFeatures Provided:CasehardenedNonstandard Thread Pitch Diameter:+0.7044/+0.7084 inchesThready Qty Per Inch (tpi):
Rib Quantity:40Thread Diameter:0.750 inchesFeatures Provided:CasehardenedNonstandard Thread Pitch Diameter:+0.7044/+0.7084 inchesThready Qty Per Inch (tpi):16
Rib Quantity:40Thread Diameter:0.750 inchesFeatures Provided:CasehardenedNonstandard Thread Pitch Diameter:+0.7044/+0.7084 inchesThready Qty Per Inch (tpi):16Hardness Rating:
Rib Quantity:40Thread Diameter:0.750 inchesFeatures Provided:CasehardenedNonstandard Thread Pitch Diameter:+0.7044/+0.7084 inchesThready Qty Per Inch (tpi):16Hardness Rating:13.0 rockwell c_and 21.0 rockwell c
Rib Quantity:40Thread Diameter:0.750 inchesFeatures Provided:CasehardenedNonstandard Thread Pitch Diameter:+0.7044/+0.7084 inchesThready Qty Per Inch (tpi):16Hardness Rating:13.0 rockwell c_and 21.0 rockwell cShoulder Shape:
Rib Quantity:40Thread Diameter:0.750 inchesFeatures Provided:CasehardenedNonstandard Thread Pitch Diameter:+0.7044/+0.7084 inchesThready Qty Per Inch (tpi):16Hardness Rating:13.0 rockwell c_and 21.0 rockwell c
Rib Quantity:40Thread Diameter:0.750 inchesFeatures Provided:CasehardenedNonstandard Thread Pitch Diameter:+0.7044/+0.7084 inchesThready Qty Per Inch (tpi):16Hardness Rating:13.0 rockwell c_and 21.0 rockwell cShoulder Shape:
Rib Quantity:40Thread Diameter:0.750 inchesFeatures Provided:CasehardenedNonstandard Thread Pitch Diameter:+0.7044/+0.7084 inchesThready Qty Per Inch (tpi):16Hardness Rating:13.0 rockwell c and 21.0 rockwell cShoulder Shape:Ribbed first shoulderMaterial:Steel
Rib Quantity:40Thread Diameter:0.750 inchesFeatures Provided:CasehardenedNonstandard Thread Pitch Diameter:+0.7044/+0.7084 inchesThready Qty Per Inch (tpi):16Hardness Rating:13.0 rockwell c and 21.0 rockwell cShoulder Shape:Ribbed first shoulderMaterial:SteelThread Series Designator:
Rib Quantity: 40 Thread Diameter: 0.750 inches Features Provided: Casehardened Nonstandard Thread Pitch Diameter: +0.7044/+0.7084 inches Thready Qty Per Inch (tpi): 16 Hardness Rating: 13.0 rockwell c and 21.0 rockwell c Shoulder Shape: Ribbed first shoulder Material: Steel Thread Series Designator: Unf
Rib Quantity:40Thread Diameter:0.750 inchesFeatures Provided:CasehardenedNonstandard Thread Pitch Diameter:+0.7044/+0.7084 inchesThready Qty Per Inch (tpi):16Hardness Rating:13.0 rockwell c and 21.0 rockwell cShoulder Shape:Ribbed first shoulderMaterial:SteelThread Series Designator:

NSN 5306-00-757-0605

Ribbed Shoulder Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

