

View Online at <https://aerobasegroup.com/nsn/5306-00-757-5624>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.556 inches

**Fastener Length:**

3.931 inches

**Head Style:**

Hexagon

**Head Height:**

0.250 inches

**Width Between Flats:**

Between 1.240 inches and 1.253 inches

**Shoulder Diameter:**

Between 0.873 inches and 0.875 inches

**Shoulder Length:**

3.375 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole

**Concentric Hole Diameter:**

0.400 inches

**Thread Diameter:**

0.750 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

280000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.744 inches first hole

**Material:**

Steel

**Material Specification:**

Ce-0896 fscm 06848 mfr ref single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Cp-0400 type 2 fscm 06848 mfr ref single treatment response

**Style Designator:**

Concentric hole unthreaded

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0