

View Online at <https://aerobasegroup.com/nsn/5306-00-761-3251>

**Thread Direction:**

Right-hand

**Thread Length:**

0.660 inches

**Fastener Length:**

Between 3.210 inches and 3.230 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.209 inches and 0.229 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**First Diameter From Head:**

Between 0.373 inches and 0.374 inches

**Second Diameter From Head:**

Between 0.315 inches and 0.325 inches

**Third Diameter From Head:**

Between 0.373 inches and 0.374 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.540 inches and 0.560 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 2.030 inches and 2.050 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

Between 2.510 inches and 2.570 inches

**Thread Diameter:**

0.375 inches

**Nonstandard Thread Pitch Diameter:**

+0.3420 to 0.3449 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

30.0 rockwell c and 38.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

3

**Product Name:**

Navy special project

**Material:**

Stainless steel

**Material Specification:**

Ams 5616 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0