# NSN 5306-00-761-3526

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-761-3526

Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.351 inches

#### Fastener Length:

1.101 inches

#### **Head Style:**

Double hexagon

**Head Height:** 

0.187 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

#### Grip Diameter:

Between 0.3108 inches and 0.3117 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole

#### **Thread Diameter:**

0.312 inches

### Grip Length:

0.750 inches

#### Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

220000 pounds per square inch

# Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

# Distance From Head Largest Bearing Surface To Shank Hole Center:

0.982 inches first hole

## Material:

Steel

## **Material Specification:**

Sps-m-107, fscm 03680 mfr ref single material response

## Surface Treatment:

Cadmium

# Surface Treatment Specification:

Nas 672 assn standard single treatment response

# **Thread Series Designator:**

Unjf

## **Specification Data:**

26512-gb511b manufacturers standard

# NSN 5306-00-761-3526

Shear Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

