## NSN 5306-00-762-5833

Machine Bolt - Page 1 of 2

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

2a



View Online at https://aerobasegroup.com/nsn/5306-00-762-5833

0.750 inches
Fastener Length:
Between 1.156 inches and 1.187 inches
Head Style:
Hexagon
Head Height:
Between 0.140 inches and 0.172 inches
Width Between Flats:
Between 0.302 inches and 0.314 inches
Hole Diameter:
0.046 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.406 inches and 0.437 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Timoriod rioda
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi):
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 185000 pounds per square inch
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 185000 pounds per square inch Hole Configuration Style:
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 185000 pounds per square inch Hole Configuration Style: Hexagon flats
Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  185000 pounds per square inch  Hole Configuration Style:  Hexagon flats  Material:
Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  185000 pounds per square inch  Hole Configuration Style:  Hexagon flats  Material:  Nickel alloy 718
Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  185000 pounds per square inch  Hole Configuration Style:  Hexagon flats  Material:  Nickel alloy 718  Material Specification:
Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  185000 pounds per square inch  Hole Configuration Style:  Hexagon flats  Material:  Nickel alloy 718  Material Specification:  Ams 5662 assn standard single material response
Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  185000 pounds per square inch  Hole Configuration Style:  Hexagon flats  Material:  Nickel alloy 718  Material Specification:  Ams 5662 assn standard single material response  Surface Treatment:
Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  185000 pounds per square inch  Hole Configuration Style:  Hexagon flats  Material:  Nickel alloy 718  Material Specification:  Ams 5662 assn standard single material response  Surface Treatment:  Silver
Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  185000 pounds per square inch  Hole Configuration Style:  Hexagon flats  Material:  Nickel alloy 718  Material Specification:  Ams 5662 assn standard single material response  Surface Treatment:  Silver  Surface Treatment Specification:
Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  185000 pounds per square inch  Hole Configuration Style:  Hexagon flats  Material:  Nickel alloy 718  Material Specification:  Ams 5662 assn standard single material response  Surface Treatment:  Silver  Surface Treatment Specification:  Qq-s-365 federal specification single treatment response

## NSN 5306-00-762-5833

Machine Bolt - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0