NSN 5306-00-762-5833

Machine Bolt - Page 1 of 2

Thread Class:

Right-hand

Thread Length:

Thread Direction:

2a



View Online at https://aerobasegroup.com/nsn/5306-00-762-5833

0.750 inches
Fastener Length:
Between 1.156 inches and 1.187 inches
Head Style:
Hexagon
Head Height:
Between 0.140 inches and 0.172 inches
Width Between Flats:
Between 0.302 inches and 0.314 inches
Hole Diameter:
0.046 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.406 inches and 0.437 inches
Hole Quantity:
1
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32
32
32 Min. Tensile Strength (psi):
32 Min. Tensile Strength (psi): 185000 pounds per square inch
Min. Tensile Strength (psi): 185000 pounds per square inch Hole Configuration Style:
Min. Tensile Strength (psi): 185000 pounds per square inch Hole Configuration Style: Hexagon flats
Min. Tensile Strength (psi): 185000 pounds per square inch Hole Configuration Style: Hexagon flats Material:
Min. Tensile Strength (psi): 185000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Nickel alloy 718
Min. Tensile Strength (psi): 185000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Nickel alloy 718 Material Specification:
Min. Tensile Strength (psi): 185000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response
Min. Tensile Strength (psi): 185000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment:
Min. Tensile Strength (psi): 185000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Silver
Min. Tensile Strength (psi): 185000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Silver Surface Treatment Specification:
Min. Tensile Strength (psi): 185000 pounds per square inch Hole Configuration Style: Hexagon flats Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Silver Surface Treatment Specification: Qq-s-365 federal specification single treatment response

NSN 5306-00-762-5833

Machine Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0