## NSN 5306-00-762-6197

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-762-6197

Thread Direction:
Right-hand
Thread Length:
Between 0.625 inches and 0.685 inches
Fastener Length:
1.188 inches
Head Style:
Double hexagon w/hole
Head Height:
0.260 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Extended Washer Diameter:
0.375 inches
Extended Washer Thickness:
Between 0.040 inches and 0.050 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 0.502 inches and 0.562 inches
Features Provided:
Finished head
Nonstandard Thread Pitch Diameter:
+0.1644/+0.1667 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
130000 pounds per square inch
Hardness Rating:
248.0 brinell standard and 341.0 brinell standard
Minimum Yield Strength:
85000 pounds per square inch
Surface Finish:
63.0 microinches grip
Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Thread Series Designator:
Unf
Shelf Life:
N1/-

N/a

## NSN 5306-00-762-6197

Machine Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

